# **DIGIEVER Network Camera Compatibility List**

## The list is applied for DIGIEVER NVR firmware 78-2 version or later

DIGIEVER NVR supports the camera feature \* Camera does not support the feature Blank means the feature is NOT supported or verified by DIGIEVER B360° Panoramic © NVR support camera hardware dewarp setting **(S)** NVR support camera software dewarp • Camera takes more than 1CH, needed to be added via video sever method 9. People Counting Threshold Alarm 1. Audio Detection 5. Intrusion Detection IVA Event 2. Advanced Motion Detection **10.** Temperature Detection 6. Loitering Detection 3. Human Detection No.: 7. Foreign Object Detection 11. Camera Tampering Detection 4. Cross Line Detection 8. Missing Object Detection 12. Object Status Change

Update: Oct. 2024

### Supported in the NVR latest version

# Copyright DIGIEVER Corporation All Rights Reserved \* Please contact DIGIEVRE sales for updated information

Brand	Camera Model	Con	Compression Format				oom Co	ntrol	Ba	on		Advanced Function				Remark		
		MJPEG	MPEG -4	H.264	н.265	Pan/ Tilt	Optica Zoom			Digital Input	Audio (Besides HTTP)	Two- way Audio	Edge Record (RTSP)	Supported IVA	Al Search (Metadata)	Advanced Right-Click Menu	Camera Firmware/ Note	Not support in other platforms CMS, VD, SS
	Genie cameras																	
	Genie IPB2IR				*	*	*	•		*								
	Genie IPC2				*	*	*		•									
	Genie IPDCD2				*	*	*		•	•								
	Genie IPDCD2PTZ5				*			•	•	•								
	Genie IPFD2PTD				*				•	•	*							
	Genie IPFD2PTZ5				*				•	*	*							
	Genie IPMD2AF				*	*	*		•									
	Genie IPMD2AFIR				*	*	*		•									
	Genie IPMVD2				*	*	*	•	•	*	*							
	Genie IPMVD2IR			•	*	*	*	•		*	*							
	Genie IPSD2PTZ20			•	*	•	•	•	•		•							
	Genie IPSD2PTZ20/IC				*				•	•	•							
	Genie IPSD2PTZ20-C				*			•	•		•							
	Genie IPVD2AF			•	*	*		•	•	•								
	Genie IPVD2AFIR			•	*	*	•	•	•	•								
	Senie Video Server																	
	Genie NV101				*						•							

#### Note:

2. Two-way audio: ACTi, AXIS, Brickcom, Canon, Hi-Sharp, Honeywell, Hunt, Levelone, Milesight, Only, ONVIF, Risk Captur, SONY, Sunell, TOA (5-generation camera), VIVOTEK (LAN), WatchNet

3. Edge recording: ACTi, AXIS (H.264 only), Airflying, Brickcom, Chiper, Dahua, Dynacolor, Hanwha, Honeywell, HUNT, LILIN, Milesight, Only, Pinetron, SONY(H.264 only), Tecom VIVOTEK, WatchNet

4. VB Search supports Canon cameras listed in the compatible list except VB-C series.

5. Local liveview supports ImmerVersion engine codec of H.264 and MJPEG only.

6. For camera added via ONVIF protocol, please follow below steps to set up camera event (like motion detection, digital input, tampering detection) on DIGIEVER:

(1) On DIGIEVER NVR: Enable camera event on event and action management page.

(2) On camera webpage: Enable camera event on camera setting page

7. NVR supports H.264 and H.265 through ONVIF. For MJPEG format, please use Generic\_MJPEG to add the camera.

8. NVR supports Honeywell IVA through ONVIF (by Model): Motion Detection, Advanced Motion Detection, Tampering Detection, Intrusion Detection, Loitering Detection, People Counting Threshold Notice

9. Cameras are not supported in Camera Digital Output in the Event & Action Management : Canon and TOA

10. "Setting from Camera" supported brand: AXIS(5.00 or below version), Brickcom, Canon, Chiper, Dynacolor, Hunt, iCantek, IDIS, i-Pro (, LILIN, Linksys, MEDIAEDGE, Messoa, Milesight, ONLY, ONVIF, Panasonic (except for BB-HCM, BL, BB-HCE series), PROBE, Provision ISR, Samsung, SECUBEST, Sony, TOA, Topview, VIVOTEK Note: Settings from camera doesn't support MJPEG for Panasonic cameras. NVR will switch the format to H.265, H.264 or MPEG-4 if users choose MJPEG.

Copyright <sup>®</sup> DIGIEVER Corporation All Rights Reserved

1

<sup>1.</sup> More models are under integration and will be released soon.