DIGIEVER Network Camera Compatibility List

The list is applied for DIGIEVER NVR firmware 78-2 version or later

DIGIE	EVER NVR supports the camera feature	* Camera does not support the fe	eature	Blank means the feature is NOT supported or verified by DIGIEVER
@360° I	Panoramic	© NVR support camera hardware	dewarp setting	NVR support camera software dewarp
🔶 Came	era takes more than 1CH, needed to be a	added via video sever method		
	1. Audio Detection	5. Intrusion Detection	9. People Counting	; Threshold Alarm
IVA Ev	vent 2. Advanced Motion Detection	6. Loitering Detection	10. Temperature D	etection
No	.: 3. Human Detection	7. Foreign Object Detection	11. Camera Tampe	ring Detection
	4. Cross Line Detection	8. Missing Object Detection	12. Object Status C	Change

Update: Oct. 2024

Supported in the NVR latest version

Copyright ® DIGIEVER Corporation All Rights Reserved * Please contact DIGIEVRE sales for updated information

Camera Model	Compression Format Zoom Control					ntrol	Basic Function					Adva	inced Functio	on	Remark		
	MJPEG	MPEG -4	³ н.264	4 H.265	Pan/ Tilt	Optical Zoom	Digital Zoom	Motion Detection	Digital Input	Audio (Besides HTTP)	Two- way Audio	Edge Record (RTSP)	Supported IVA	Al Search (Metadata)	Advanced Right-Click Menu	Camera Firmware/ Note	Not support i other platforn CMS, VD, SS
LevelOne cameras									-				-				
LevelOne FCS-0030v1				*	*	*		•	*	•							
LevelOne FCS-0030v2	•		•	*	*	*	•	•	*	•							
LevelOne FCS-0031	•		•	*	*	*	•	•	*	•							
LevelOne FCS-1122	•			*	*	*		•	•	•							
LevelOne FCS-3061	•	•	•	*	*	*	•	•		•							
LevelOne FCS-5952	*	*	•		*	*		•		•	•	*	4, 5, 6, 9			v3.6.1602.1006.299.0.19.5.1.D01	
LevelOne SCS-2120		*			*	*		•		•			1, 11			8.8.135.3	
LevelOne SCS-2120R		*			*	*		•		•			1, 11			8.8.135.3	
LevelOne SCS-2121	*	*			*	*		•		•	*		3, 4			VA1.OH29.0641-20210302-HDXP2P-GEN	
LevelOne SCS-2121R		*			*	*		•	*	•							
LevelOne SCS-2122R		*	•		*	*		•	*	•						8.8.135.3	
LevelOne SCS-3250R		*			*	*		•	*	•						8.8.135.3	
LevelOne SCS-3320R		*		•	*	*		•	*	•						8.8.135.3	
LevelOne SCS-3321R		*	•	•	*	*		•	*	•						8.8.135.3	
LevelOne SCS-3550R		*	•	•	*	*	•	•	*	•						8.8.135.3	
LevelOne SCS-5151	*	*			*	*		•		•	*		3, 4			VA1.OH29.0641-20210302-HDXP2P-GEN	
LevelOne SCS-5151R		*		•	*	*		•	*	•							
LevelOne SCS-5152R		*	•		*	*		•	*	•						8.8.135.3	
LevelOne SCS-6210R		*	•	•	*	*	•	•	•	•			1, 11			8.8.135.3 (audio detection, tampering detection)	
LevelOne SCS-7220R		*		•	*	*		•		•			1, 11			8.8.135.3 (audio detection, tampering detection)	
LevelOne SCS-7221R		*	•	•	*	*		•	*	•						8.8.135.3	
LevelOne SCS-7250R		*	•	•	*	*	•	•	*	•						8.8.135.3	
LevelOne WCS-0030v1			•	*	*	*		•	*	•							
LevelOne WCS-0030v2			•	*	*	*		•	*	•							
LevelOne WCS-0050	•			*	*	*		•	*	•							
(DIGIEVER NVR supports LevelOne cameras with ONVIF)																
LevelOne SC-8200	*	*		*	*	*		*	*	*							
LevelOne V82-DV103	*	*		*	*	*		*	*	*							
LevelOne SCS-6370	*	*	•		•		•	•	*	•					Moving Speed(PTZ), Wiper	V1.0.6 Build 201710101707-r2368D	

Note:

1. More models are under integration and will be released soon.

2. Two-way audio: ACTi, AXIS, Brickcom, Canon, Hi-Sharp, Honeywell, Hunt, Levelone, Milesight, Only, ONVIF, Risk Captur, SONY, Sunell, TOA (5-generation camera), VIVOTEK (LAN), WatchNet

3. Edge recording: ACTi, AXIS (H.264 only), Airflying, Brickcom, Chiper, Dahua, Dynacolor, Hanwha, Honeywell, HUNT, LILIN, Milesight, Only, Pinetron, SONY(H.264 only), Tecom VIVOTEK, WatchNet

4. VB Search supports Canon cameras listed in the compatible list except VB-C series.

5. Local liveview supports ImmerVersion engine codec of H.264 and MJPEG only.

6. For camera added via ONVIF protocol, please follow below steps to set up camera event (like motion detection, digital input, tampering detection) on DIGIEVER:

(1) On DIGIEVER NVR: Enable camera event on event and action management page.

(2) On camera webpage: Enable camera event on camera setting page

7. NVR supports H.264 and H.265 through ONVIF. For MJPEG format, please use Generic_MJPEG to add the camera.

8. NVR supports Honeywell IVA through ONVIF (by Model): Motion Detection, Advanced Motion Detection, Tampering Detection, Intrusion Detection, Loitering Detection, People Counting Threshold Notice

9. Cameras are not supported in Camera Digital Output in the Event & Action Management : Canon and TOA

10. "Setting from Camera" supported brand: AXIS(5.00 or below version), Brickcom, Canon, Chiper, Dynacolor, Hunt, iCantek, IDIS, i-Pro (, LILIN, Linksys, MEDIAEDGE, Messoa, Milesight, ONLY, ONVIF, Panasonic (except for BB-HCM, BL, BB-HCE series), PROBE, Provision ISR, Samsung, SECUBEST, Sony, TOA, Topview, VIVOTEK Note: Settings from camera doesn't support MJPEG for Panasonic cameras. NVR will switch the format to H.265, H.264 or MPEG-4 if users choose MJPEG.

Copyright [®] DIGIEVER Corporation All Rights Reserved