

DIGIEVER Network Camera Compatibility List

The list is applied for DIGIEVER NVR firmware 78-2 version or later

Update: Oct. 2024

- DIGIEVER NVR supports the camera feature
- Ⓢ 360° Panoramic
- ◆ Camera takes more than 1CH, needed to be added via video sever method
- 1. Audio Detection
- 2. Advanced Motion Detection
- No.: 3. Human Detection
- 4. Cross Line Detection
- * Camera does not support the feature
- Ⓢ NVR support camera hardware dewarp setting
- 5. Intrusion Detection
- 6. Loitering Detection
- 7. Foreign Object Detection
- 8. Missing Object Detection
- Blank means the feature is NOT supported or verified by DIGIEVER
- Ⓢ NVR support camera software dewarp
- 9. People Counting Threshold Alarm
- 10. Temperature Detection
- 11. Camera Tampering Detection
- 12. Object Status Change

Supported in the NVR latest version

Copyright © DIGIEVER Corporation All Rights Reserved

* Please contact DIGIEVER sales for updated information

Brand	Camera Model	Compression Format				Zoom Control			Basic Function				Advanced Function			Remark		
		MJPEG	MPEG-4	H.264	H.265	Pan/Tilt	Optical Zoom	Digital Zoom	Motion Detection	Digital Input	Audio (Besides HTTP)	Two-way Audio	Edge Record (RTSP)	Supported IVA	AI Search (Metadata)	Advanced Right-Click Menu	Camera Firmware/ Note	Not support in other platforms CMS, VD, SS
Tescom	Tescom cameras																	
	Tescom TNC-3000		●	●	*	*	*	●										
	Tescom TNC-3030		●	●	*	*	*	●										
	Tescom TNC-3100		●	●	*	*	*	●										
	Tescom TNC-3200		●	●	*	*	*	●										

Note:

- More models are under integration and will be released soon.
 - Two-way audio: ACTi, AXIS, Brickcom, Canon, Hi-Sharp, Honeywell, Hunt, Levelone, Milesight, Only, ONVIF, Risk Captur, SONY, Sunell, TOA (5-generation camera), VIVOTEK (LAN), WatchNet
 - Edge recording: ACTi, AXIS (H.264 only), Airflying, Brickcom, Chiper, Dahua, Dynacolor, Hanwha, Honeywell, HUNT, LILIN, Milesight, Only, Pinetron, SONY(H.264 only), Tecom VIVOTEK, WatchNet
 - VB Search supports Canon cameras listed in the compatible list except VB-C series.
 - Local liveview supports ImmerVersion engine codec of H.264 and MJPEG only.
 - For camera added via ONVIF protocol, please follow below steps to set up camera event (like motion detection, digital input, tampering detection) on DIGIEVER:
 - On DIGIEVER NVR: Enable camera event on event and action management page.
 - On camera webpage: Enable camera event on camera setting page
 - NVR supports H.264 and H.265 through ONVIF. For MJPEG format, please use Generic_MJPEG to add the camera.
 - NVR supports Honeywell IVA through ONVIF (by Model): Motion Detection, Advanced Motion Detection, Tampering Detection, Intrusion Detection, Loitering Detection, People Counting Threshold Notice
 - Cameras are not supported in Camera Digital Output in the Event & Action Management : Canon and TOA
 - "Setting from Camera" supported brand: AXIS(5.00 or below version), Brickcom, Canon, Chiper, Dynacolor, Hunt, iCantek, IDIS, i-Pro (, LILIN, Linksys, MEDIAEDGE, Messoa, Milesight, ONLY, ONVIF, Panasonic (except for BB-HCM, BL, BB-HCE series), PROBE, Provision ISR, Samsung, SECUBEST, Sony, TOA, Topview, VIVOTEK
- Note: Settings from camera doesn't support MJPEG for Panasonic cameras. NVR will switch the format to H.265, H.264 or MPEG-4 if users choose MJPEG.

Copyright © DIGIEVER Corporation All Rights Reserved