## **DIGIEVER Network Camera Compatibility List**

## The list is applied for DIGIEVER NVR firmware 78-2 version or later

Update: Oct. 2024

	EVER NVR supports the camera feature Panoramic	* Camera does not support the feature © NVR support camera hardware dewarp	Blank means the feature is NOT supported or verified by DIGIEVER setting
🔶 Cam	era takes more than 1CH, needed to be a	added via video sever method	
	1. Audio Detection	5. Intrusion Detection	9. People Counting Threshold Alarm
IVA E	vent 2. Advanced Motion Detection	6. Loitering Detection	10. Temperature Detection
No	.: 3. Human Detection	7. Foreign Object Detection	11. Camera Tampering Detection
	4. Cross Line Detection	8. Missing Object Detection	12. Object Status Change

## Supported in the NVR latest version

## 

Brand	Camera Model	Compression Format			Zoom Control		Basic Function				Advanced Function				Remark			
		MJPEG	MPEG -4	H.264	H.265	Pan/ Tilt	Optical Zoom	Digital Zoom	Motion Detection	Digital Input	Audio (Besides HTTP)	Two- way Audio	Edge Record (RTSP)	Supported IVA	Al Search (Metadata)	Advanced Right-Click Menu	Camera Firmware/ Note	Not support in other platforms CMS, VD, SS
TANTOS	TANTOS cameras																	
	TANTOS TSI-C111F				*	*	*		•									
	TANTOS TSI-C111F Wi-Fi	•	•	•	*	*	*		•		•							
	TANTOS TSI-C211F	•		•	*	*	*	•	•		•							
	TANTOS TSI-C211F WI-Fi	•			*	*	*		•		•							
	TANTOS TSI-C311F			•	*	*	*		•		•							

Note:

2. Two-way audio: ACTi, AXIS, Brickcom, Canon, Hi-Sharp, Honeywell, Hunt, Levelone, Milesight, Only, ONVIF, Risk Captur, SONY, Sunell, TOA (5-generation camera), VIVOTEK (LAN), WatchNet

3. Edge recording: ACTi, AXIS (H.264 only), Airflying, Brickcom, Chiper, Dahua, Dynacolor, Hanwha, Honeywell, HUNT, LILIN, Milesight, Only, Pinetron, SONY(H.264 only), Tecom VIVOTEK, WatchNet

4. VB Search supports Canon cameras listed in the compatible list except VB-C series.

5. Local liveview supports ImmerVersion engine codec of H.264 and MJPEG only.

6. For camera added via ONVIF protocol, please follow below steps to set up camera event (like motion detection, digital input, tampering detection) on DIGIEVER:

(1) On DIGIEVER NVR: Enable camera event on event and action management page.

(2) On camera webpage: Enable camera event on camera setting page

7. NVR supports H.264 and H.265 through ONVIF. For MJPEG format, please use Generic\_MJPEG to add the camera.

8. NVR supports Honeywell IVA through ONVIF (by Model): Motion Detection, Advanced Motion Detection, Tampering Detection, Intrusion Detection, Loitering Detection, People Counting Threshold Notice

9. Cameras are not supported in Camera Digital Output in the Event & Action Management : Canon and TOA

10. "Setting from Camera" supported brand: AXIS(5.00 or below version), Brickcom, Canon, Chiper, Dynacolor, Hunt, iCantek, IDIS, i-Pro (, LILIN, Linksys, MEDIAEDGE, Messoa, Milesight, ONLY, ONVIF, Panasonic (except for BB-HCM, BL, BB-HCE series), PROBE, Provision ISR, Samsung, SECUBEST, Sony, TOA, Topview, VIVOTEK Note: Settings from camera doesn't support MJPEG for Panasonic cameras. NVR will switch the format to H.265, H.264 or MPEG-4 if users choose MJPEG.

Copyright <sup>®</sup> DIGIEVER Corporation All Rights Reserved

<sup>1.</sup> More models are under integration and will be released soon.