

DIGIEVER Network Camera Compatibility List

The list is applied for DIGIEVER NVR firmware 78-2 version or later

Update: Oct. 2024

● DIGIEVER NVR supports the camera feat * Camera does not support the feature Blank means the feature is NOT supported or verified by DIGIEVER

Ⓟ 360° Panoramic Ⓞ NVR support camera hardware dewarp setting

Ⓢ NVR support camera software dewarp

◆ Camera takes more than 1CH, needed to be added via video sever method

- | | | | |
|----------------|------------------------------|-----------------------------|------------------------------------|
| IVA Event No.: | 1. Audio Detection | 5. Intrusion Detection | 9. People Counting Threshold Alarm |
| | 2. Advanced Motion Detection | 6. Loitering Detection | 10. Temperature Detection |
| | 3. Human Detection | 7. Foreign Object Detection | 11. Camera Tampering Detection |
| | 4. Cross Line Detection | 8. Missing Object Detection | 12. Object Status Change |

Supported in the NVR latest version

Copyright © DIGIEVER Corporation All Rights Reserved * Please contact DIGIEVER sales for updated information

Brand	Camera Model	Compression Format				Zoom Control			Basic Function					Advanced Function			Remark			
		MJPEG	MPEG-4	H.264	H.265	Pan/Tilt	Optical Zoom	Digital Zoom	Motion Detection	Digital Input	Audio (Besides HTTP)	Two-way Audio	Edge Record (RTSP)	Supported IVA	AI Search (Metadata)	Advanced Right-Click Menu		Camera Firmware/ Note	Not support in other platforms CMS, VD, SS	
Milesight	Milesight cameras																			
	Milesight MS-C2961-EPB		*	●	●	●	●	●	●	●	*				2, 3			43.7.0.72-LPR1-r18		
	Milesight MS-C2961-QELPB		*	●	●	●	●	●	●	●	*	*						43.7.0.72-LPR1-r18		
	Milesight MS-C2961-QEPB		*	●	●	●	●	●	●	●	*							43.7.0.72-LPR1-r18		
	Milesight MS-C2961-RELPB		*	●	●	●	●	●	●	●	*	*						43.7.0.72-LPR1-r6		
	Milesight MS-C2961-REPB		*	●	●	●	●	●	●	●	*	*						43.7.0.72-LPR1-r6		
	Milesight MS-C2962-RFPC	*	*	●	●	*	●	●	●	●	●	●	●					45.8.0.3-r10		
	Milesight MS-C2962-RFPE	*	*	●	●	*	●	●	●	●	●	*	*		1, 4, 9			61.8.85.3-r6		
	Milesight MS-C2963-PB	*	*	●	●	*	*	●	●	●	●							40.7.0.58-r1		
	Milesight MS-C2964-FPE	*	*	●	●	*	●	●	●	*	*		●		2, 3, 4, 6, 7, 8, 9, 11			61.8.85.4-c4-t18		
	Milesight MS-C2964-PB	*	*	●	●	*	●	●	●	*	*		●		2, 3, 4, 6, 7, 8, 9, 11			40.7.1.80-r4		
	Milesight MS-C2964-PD	*	*	*	●	●	*	*	●	●	*	*	●		4			51.7.85.77-r4		
	Milesight MS-C2966-RFPE	*	*	●	●	*	●	●	●	*	*		●		2, 3, 4, 6, 7, 8, 9, 11			61.8.85.4-c4-t18		
	Milesight MS-C2967-X12RPE	*	*	●	●	●	●	●	●	●	●	●	●					61.8.0.4-r4-a2		
	Milesight MS-C2972-FIPB		*	●	●	*	●	●	●	●	●	●	●					40.7.0.74		
	Milesight MS-C2972-FPB	*	*	●	●	*	*	●	●	●	*							40.7.0.60-r17		
	Milesight MS-C2972-RFLPE	*	*	●	●	*	●	●	●	●	●	●	●					T_61.8.0.3_EU-r12		
	Milesight MS-C2973-PD	*	*	●	●	*	●	●	●	*	*		●		2, 3, 4, 6, 7, 8, 9, 11			61.8.85.4-c4-t18		
	Milesight MS-C5363-FPB		*	●	●	*	●	●	●	*	*							41.7.0.67-r10 * Support people counting and cross-line detection *For tripwire display on liveview, system only display one type of tripwire, either people counting or cross line tripwire.		
	Milesight MS-C5363-PB	*	*	●	●	*	*	●	●	*	*							41.7.0.60-r14		
	Milesight MS-C5364-FPA	*	*	●	●	*	●	●	●	●	●	●	●					31.8.0.3-r10		
	Milesight MS-C5372-FPE	*	*	●	●	*	●	●	●	*	*		●		2, 3, 4, 6, 7, 8, 9, 11			61.8.85.4-c4-t18		
	Milesight MS-C5373-PB	*	*	●	●	*	*	●	●	*	●									
	Milesight MS-C5375-EPC	*	*	●	●	*	●	●	●	●	●	●	●					45.8.0.3-r10		
	Milesight MS-C8164-FIPB		*	●	●	*	●	●	●	*	*	*						43.7.0.74		
	Milesight MS-C8262-FIPB	*	*	●	●	*	●	●	●	●	●							43.7.0.61-r17		
	Milesight MS-C8266-FIPA	*	*	●	●	*	●	●	●	●	●	●	●					31.8.0.3-r10		
	Milesight MS-C9674-PB	*	*	●	●	*	*	●	●	●	●	*						43.7.0.73-t8		

Note:

- More models are under integration and will be released soon.
- Two-way audio: ACTi, AXIS, Brickcom, Canon, Hi-Sharp, Honeywell, Hunt, Levelone, Milesight, Only, ONVIF, Risk Captur, SONY, Sunell, TOA (5-generation camera), VIVOTEK (LAN), WatchNet
- Edge recording: ACTi, AXIS (H.264 only), Airflying, Brickcom, Chiper, Dahua, Dynacolor, Hanwha, Honeywell, HUNT, LILIN, Milesight, Only, Pinetron, SONY(H.264 only), Tecom VIVOTEK, WatchNet
- VB Search supports Canon cameras listed in the compatible list except VB-C series.
- Local liveview supports ImmerVersion engine codec of H.264 and MJPEG only.
- For camera added via ONVIF protocol, please follow below steps to set up camera event (like motion detection, digital input, tampering detection) on DIGIEVER:

Brand	Camera Model	Compression Format				Zoom Control			Basic Function			Advanced Function				Remark	
		MJPEG	MPEG-4	H.264	H.265	Pan/Tilt	Optical Zoom	Digital Zoom	Motion Detection	Digital Input	Audio (Besides HTTP)	Two-way Audio	Edge Record (RTSP)	Supported IVA	AI Search (Metadata)	Advanced Right-Click Menu	Camera Firmware/ Note

(1) On DIGIEVER NVR: Enable camera event on event and action management page.

(2) On camera webpage: Enable camera event on camera setting page

7. NVR supports H.264 and H.265 through ONVIF. For MJPEG format, please use Generic_MJPEG to add the camera.

8. NVR supports Honeywell IVA through ONVIF (by Model): Motion Detection, Advanced Motion Detection, Tampering Detection, Intrusion Detection, Loitering Detection, People Counting Threshold Notice

9. Cameras are not supported in Camera Digital Output in the Event & Action Management : Canon and TOA

10. "Setting from Camera" supported brand: AXIS(5.00 or below version), Brickcom, Canon, Chiper, Dynacolor, Hunt, iCantek, IDIS, i-Pro (, LILIN, Linksys, MEDIAEDGE, Messoa, Milesight, ONLY, ONVIF, Panasonic (except for BB-HCM, BL, BB-HCE series), PROBE, Provision ISR, Samsung, SECUBEST, Sony, TOA, Topview, VIVOTEK

Note: Settings from camera doesn't support MJPEG for Panasonic cameras. NVR will switch the format to H.265, H.264 or MPEG-4 if users choose MJPEG.

Copyright © DIGIEVER Corporation All Rights Reserved